

MARCH PUMPS

BC-2-MD Brush Type and Brushless


1819 PICKWICK AVE., GLENVIEW, IL 60026-1306, U.S.A PHONE: (847) 729-5300 - FAX: (847) 729-7062 WWW.MARCHPUMP.COM

DESCRIPTION & OPERATION:


Series 2 are centrifugal magnetic drive pumps, eliminating the need for a shaft seal. Pumps can be serviced with a screwdriver. See the parts list for a breakdown of parts. Pumps are not self-priming, lack a suction lift, and thus require a **flooded suction**. Pumps **cannot be run dry** because the impeller requires the liquid being pumped for lubrication. For liquids with a specific gravity greater than water, have a higher viscosity, or for elevated temperatures, a trimmed impeller may be necessary. Brushless motors must be operated within a restricted voltage range due to the electronics. For application assistance, contact March Pump.

Brushtype Motor : 9" Leads, Red is positive, Black is negative

Brushless Motor: 11.5" Leads, Red is positive, Black is negative. Restricted Voltage Range: 14V-30V



Specifications		BC-2CP-MD Brush Type							BC-2CP-	MD Bru	shless	BC-2K-MD Brushless
Product	12V		0125-0123-0100						Not	Availab	le	Not Available
	24V		0125-0123-0200						0125	-0123-04	400	0125-0138-0300
Inlet-Outlet	3/8"FPT & 3/4"MPT-1/4"MPT 3/8"FPT & 3/4"MPT-1/4"MPT						-1/4"MPT	3/8"FPT & 3/4"MPT-1/4"MPT				
Max Internal Pressure			50PSI (344 kPa)						50PS	I (344 k	Pa)	75PSI (517 kPa)
Max Liquid Temperature		190F (87C)					190F (87C)				200F (93C)	
Max F		Flow	М	Max Head			E	Electrical			Packed Weight	
Model	GPM	LPM	FT	PSI	М	Voltage	Amps	HP	kW	RPM	Pounds	
BC-2CP-MD Brushtype	6	22.7	15	6.5	4.6	12/24	3.5/1.	8 1/25	0.029	3650	4	
BC-2C-MD Brushless	6.2	23.4	29	12.5	8.8	24	2.1	1/25	0.029	3800	4	
All specifications & data are based on pumping water & are intended as a guideline only. Specifications may vary with different motors.												



NOTE: When attaching the Drive Magnet to the motor shaft, position the face of the Drive Magnet 1/16 inch below the face of the Motor Bracket.									
BC-2CP-MD Brushtype							BC-2CP-MD Brushless		
Item	Part Number	QTY REQ	Description	ltem	Part Number	QTY REQ	Description		
1	0115-0062-1000	6	#7-19 x 1-7/16" Long Self-Tapping Screw (Stainless)	1	0115-0062-1000	6	#7-19 x 1-7/16" Long Self-Tapping Screw (Stainless)		
2	0125-0056-1000	1	Cover with 3/8" FPT x 3/4" MPT Inlet (Polypropylene)	2	0125-0056-1000	1	Cover with 3/8" FPT x 3/4" MPT Inlet (Polypropylene)		
3	0125-0065-1000	1	3/32" CS x 2-3/16" OD "O" Ring (Viton)	3	0125-0065-1000	1	3/32" CS x 2-3/16" OD "O" Ring (Viton)		
4	0130-0028-1000	1	Thrust Washer (Ceramic)	4	0130-0028-1000	1	Thrust Washer (Ceramic)		
5	0125-0061-1000	1	Shaft (Ceramic)	5	0125-0061-1000	1	Shaft (Ceramic)		
6	0125-0087-0200	1	Encapsulated Impeller (Polypropylene)	6	0125-0087-0200	1	Encapsulated Impeller (Polypropylene)		
7	0125-0058-1000	1	Rear Housing with 1/4"MPT Outlet (Polypropylene)	7	0125-0058-1000	1	Rear Housing with 1/4"MPT Outlet (Polypropylene)		
8	0125-0083-0100	1	0.250" Bore Drive Magnet	11	0125-0083-0200	1	6MM Bore Drive Magnet		
9	0210-0036-100	4	#8-32 x 3/4"Lg. Screw (Stainless)	9	0210-0036-100	4	#8-32 x 3/4"Lg. Screw (Stainless)		
10	0858-0004-1000	4	#8 Washer (Stainless)	10	0858-0004-1000	4	#8 Washer (Stainless)		
11	0125-0069-1000	1	Motor Bracket (Plastic)	11	0125-0069-1000	1	Motor Bracket (Plastic)		
12	0125-0106-1000	1	Base (Plastic)	12	0125-0106-1000	1	Base (Plastic)		
13A	0809-0101-1000	1	Motor, 12V, DC	13C	0125-0128-1000	1	Motor, 24V, DC		
13B	0809-0103-1000	1	Motor, 24V, DC						
			BC-2K-MD Brushless						
	•	r materials and/or parts not listed. lable upon special order.	Item	Part Number	QTY REQ	Description			
	rials in contact wit			1	0115-0062-1000	6	#7-19 x 1-7/16" Long Self-Tapping Screw (Stainless)		
	C-MD: Polypropyle			2	0125-0136-1000	1	Cover with 3/8" FPT x 3/4" MPT Inlet (Glass Filled Kynar)		
			umps are guaranteed only against defects in	3	0125-0065-1000	1	3/32" CS x 2-3/16" OD "O" Ring (Viton)		
	•		period of one year from date of manufacture pumping nty and to register online go to www.marchpump.com/	4	0130-0028-1000	1	Thrust Washer (Ceramic)		
	nty-registration			5	0125-0061-1000	1	Shaft (Ceramic)		
				6	0125-0101-0200	1	Encapsulated Impeller (Glass Filled Kynar		
				7	0125-0137-1000	1	Rear Housing with 1/4"MPT Outlet (Glass Filled Kynar)		
				11	0125-0083-0200	1	6MM Bore Drive Magnet		
				9	0210-0036-100	4	#8-32 x 3/4"Lg. Screw (Stainless)		
				10	0858-0004-1000	4	#8 Washer (Stainless)		
				11	0125-0069-1000	1	Motor Bracket (Plastic)		
				12	0125-0106-1000	1	Base (Plastic)		
				13C	0125-0128-1000	1	Motor, 24V, DC		